

WiMER4A is the wireless transmitter for Mitutoyo digital protractor 950-318. Mitutoyo 950-318 is a gravity electronic sensor based digital protractor. It covers measurement range of 360° (90°x4) with high resolution and high accuracy. It features a machined aluminum frame with an easy-to-read liquid crystal display.

Features:

- · Continuous wireless reading of 0-360° in software
- · Bluetooth Low Energy Technology
- Multiple platform support (iOS, Android, PC)
- · Continuous and single modes data recording

WiMFR4A

Rechargeable battery

Compatible with Mitutoyo Protractor 950-318





WiMER4A	Specification
Measurement Range	360° (in software), 90°x4 (on gage)
Resolution	0.01° (0° to 9.99°), 0.1° (10° to 90°)
Accuracy	0.05° (0° to 10°), 0.2° (10° to 80°), 0.1° (80° to 90°)
Wireless Data Rate	2 HZ
Transmission Range	20 m (indoors)/30 m (outdoors)
Dimensions	2.50 x 1.63 x 0.80 in
Working Temperature	0 - 50 °C
Battery	400 mAh
Battery Life	30 hrs
Charging	5 VDC USB

Mitutoyo

.035

More Features with our FREE Apps/Software*

Multiple devices simultaneous reading

Windows

· Data plot on iPhone/iPad

Mitutoyo
Digital Protractor

- · Continuous or Single data recording
- · Max, Min, TIR measurement
- · Remote zeroing from the App
- Real-time cloud data streaming to worldwide
- Custom formula calculator
- · Large analog probe meter with adjustable range
- · Measurement voice read in 9 languages
- · Data export in CSV via Email and cloud drives
- · Keyboard entry to Excel or SPC software on PC
- Apple Watch support



*Availability of features vary between Apps/platforms